

Model code : ISM3018D-<N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>-FC/SC-48w

	ISM3018D	N1	N2	GSFP	N3	F	L	W	FC/SC	48w	
Nomenclature	Code	Subseries	No. of T(X) ports	No. of type-I FX ports	No. of type-II FX ports	M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance is	Transmit/receive wavelength:	Connctor type:	Power supply voltage	
	Description		20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	FC、SC optional	wide voltage 48VDC (18~72 VDC)					
Example	ISM3018D-12T-2GSFP-4B6035-FC-48w ISM3018D-12T-2GSFP-2B6035-2M3-FC-48w ISM3018D-14T-2GSFP-2M3-SC-48w ISM3018D-16T-2GSFP-48w										
Optional port combinations (i.e. <N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>部分)	T(X) port			12T			14T		16T		
	FX port			Type-I FX ports : 4	Type-I FX ports : 2	Type-I FX ports : 4	Type-I FX ports : 0				
				Type-II FX ports : 0	Type-II FX ports : 2	Type-II FX ports : 0	Type-II FX ports : 0				
				4M3	2S203-2M3	4M3	-				
			4S203	2S205-2M3	4S203	-					



		4S205	2S403-2M3	4S205	-
		4S403	2S405-2M3	4S403	-
		4S405	2S603-2M3	4S405	-
		4S603	2S605-2M3	4S603	-
		4S605	2S803-2M3	4S605	-
		4S803	2S805-2M3	4S803	-
		4S805	2B2053-2M3	4S805	-
		4B2053	2B2035-2M3	4B2053	-
		4B2035	2B4053-2M3	4B2035	-
		4B4053	2B4035-2M3	4B4053	-
		4B4035	2B6053-2M3	4B4035	-
		4B6053	2B6035-2M3	4B6053	-
		4B6035		4B6035	-