

Model code : ISM3028U-4GSFP-8T-8T-<N1>T-<N2><F><L><W>-FC/SC-HV/HV-HV

Model code : ISM3028U-4GSFP-8T-8T-<N1>T-<N2><F><L><W>-FC/SC-HV/HV-HV											
		ISM3028U	4GSFP	8T	N1	N2	F	L	W	FC/SC	HV/HV-HV
Nomenclature	Code										
	Description	Subseries	4 Gigabit SFP or without SPF Gigabit	8 fixed T(X)	No. of T(X) ports	No. of FX ports	Optical fibre type: M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	Transmit/receive wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connector type: FC、SC optional	Single/Dual redundant power supply
Example		ISM3028U-4GSFP-8T-8T-8T-HV ISM3028U-4GSFP-8T-8T-4T-4S203SC-HV									
Optional port combinations				T(X) port			0T (omitted)	2T	4T	6T	8T
(i.e. <N1>T-<N2><F><L><W>-<N3><F><L><W>section)							No. of FX ports : 8	No. of FX ports : 6	No. of FX ports : 4	No. of FX ports : 2	No. of FX ports : 0
							8M3	6M3	4M3	2M3	-



8S203	6S203	4S203	2S203	-
8S205	6S205	4S205	2S205	-
8S403	6S403	4S403	2S403	-
8S405	6S405	4S405	2S405	-
8S603	6S603	4S603	2S603	-
8S605	6S605	4S605	2S605	-
8S803	6S803	4S803	2S803	-
8S805	6S805	4S805	2S805	-
8B2053	6B2053	4B2053	2B2053	-
8B2035	6B2035	4B2035	2B2035	-
8B4053	6B4053	4B4053	2B4053	-
8B4035	6B4035	4B4035	2B4035	-
8B6053	6B6053	4B6053	2B6053	-
8B6035	6B6035	4B6035	2B6035	-