

**Model code : ISE3018D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24**

		ISE3018D	N1	N2	F	L	W	FC/SC	24
<b>Nomenclature</b>	<b>Code</b>				Optical fibre type:		Transmit/receive wavelength:		Power supply voltage
	<b>Description</b>	Subseries	No. of T(X) ports	No. of FX ports	M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	3:Tx1310/R x1310nm 5:Tx1550/R x1550nm 53:Tx1550/R x1310nm 35:Tx1310/R x1550nm	Conncetortype: FC、 SC optional:	( 12~36V DC )
<b>Example</b>		ISE3018D-14T-2GSFP-2M3-FC-24 ISE3018D-14T-2GSFP-2S203-SC-24 ISE3018D-16T-2GSFP-24							
<b>Optional port combinations</b> (i.e.<N1>T-2GSFP-<N2><F><L><W>-section )				<b>T(X) ports</b>		14T		16T	
				<b>FX ports</b>		No. of FX ports : 2		No. of FX ports : 0	
						2M3		-	
						2S203		-	
						2S205		-	
				2S403		-			

		2S405	-
		2S603	-
		2S605	-
		2S803	-
		2S805	-
		2B2053	-
		2B2035	-
		2B4053	-
		2B4035	-
		2B6053	-
		2B6035	-