

Model code : ISF2016D-<N1>T-<N2><F><L><W>-FC/SC-24

Model code : ISF2016D-<N1>T-<N2><F><L><W>-FC/SC-24									
		ISF2016D	N1	N2	F	L	W	FC/SC	24
Nomenclature	Code				Optical fibre type:		Transmit/receive		
	Description	Subseries	No. of T(X) ports	No. of FX ports	M: Multi-mode dual-fibre S: Single-mode dual-fibre B: Single-mode single-fibre	Transmission distance: 20/40/60/80 /120 (Multimode distance is 2KM, default is omitted.)	wavelength: 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	Connctor type: FC、SC optional	Power supply voltage (12~36VDC)
	Example	ISF2016D-14T-2M3-FC-24			ISF2016D-14T-2S203-SC-24				
Optional port combinations (i.e.<N1>T-<N2><F><L><W>-section)					T(X) port		14T		
					FX port		No. of FX ports : 2		
							2M3		
							2S203		
							2S205		
							2S403		
							2S405		

2S603

2S605

2S803

2S805

2B2053

2B2035

2B4053

2B4035

2B6053

2B6035